cofluid

Hydraulics Power Units & Hose Processing Equipment

Pressa verticale
Vertical crimping machine

V30ELAP

MADE IN ITALY CE

DESCRIZIONE / *Description*

- Pressa verticale elettrica a pedale, completa di centralina oleodinamica a 2 velocità, per tubi fino a 3/4” 4SP - 1” R2, anche curva+ curva.
- *Vertical crimping machine controlled by pedal, with two-speed hydraulic control unit, for hydraulic hoses up to 3/4” 4SP - 1” R2, suitable also for elbow + elbow.*

SCHEDA TECNICA / *Data Sheet*

Potenza di pressatura / *Crimping force*	80Ton *(88,18 US TONS)*
Range di pressatura / *Operating range*	7-45mm *(0,27”-1,77”)*
Diametro di pressatura massimo / *Max diameter pressing*	-
Tubo 6 spirali / *6 spirals hose*	-
Tubo 4 spirali / *4 spirals hose*	3/4”*
Tubo 2 trecce / *2 braids hoses*	1”*
Apertura morsetti / *Die opening*	-
Diametro massimo di apertura / *Max diameter opening*	-
Motore / *Power*	1,5kw *(2Hp)*
Voltaggio Standard / *Standard voltage*	400V-50/60Hz
Dimensione LxPxH / *Dimensions LxWxH*	350x600x800mm *(23,78”x23,62”x31,5”)*
Peso senza olio / *Dry weight*	67 Kg *(147,7 Lbs)*
Olio / *Oil*	10 L

☑ = di serie / *standard*

ACCESSORI / *Accessories*

☑	Controllo EL *EL Control*	☑	Base con centralina e box portamorsetti *Base unit with door and box dies*	☑	Doppia velocità *Double speed*
☑	Riapertura automatica della testa *Automatic opening of the crimping head*	☑	Micron di regolazione riapertura testa *Micron reopening head adjustment*	☑	Nonio graduato per regolazione Ø di pressatura *Graduated nonius adjustment for the pressing diameter*
☐	Morsetti speciali *Special dies*	☐	Voltaggio speciale *Special voltage*	☐	Morsetti freno *Brakes dies*
☐	Morsetti freon *Refrigerant dies*	☐		☐	
☐		☐		☐	
☐		☐		☐	

MORSETTI / *Dies*

Ø (mm)	7	10	13	16	19	22	25	30	38
L (mm)	50	50	50	50	50	50	50	50	50

* Valore indicativo in funzione del prodotto da pressare / *Indicative value depending on the product which needs to be crimped*

COFLUID S.r.l. Via Gobetti, 34 - 52100 - AREZZO - ITALY - Tel. 0575.300209 - www.cofluid.it info@cofluid.it